

Notebook Quick Reference

Globalyst	130	200S	250P
PROCESSOR Clock Speed Options Cache	Intel 486 DX2/50 8KB	Intel 486 DX4/75MHz DX4/100MHz 8KB	Intel Pentium 75MHz Asynchronous 256KB
MEMORY Standard Maximum Hard Disk Options	4MB 20MB 260MB or 340MB fixed	4MB 20MB 260MB or 340MB removable	8MB 40MB 540MB or 810MB removable
DRIVE BAYS Flex Disk Options Tape Drive Options CD ROM Options	3.5" 1.44MB fixed None None	3.5" 1.44MB fixed None None	3.5" 1.44MB removable 2.0GB SCSI DAT 600 MB SCSI (quad speed) or 600MB IDE (quad speed)
INPUT / OUTPUT SLOTS PCMCIA Business Audio I/O Interfaces Keyboard Trackball	1 Type I or 1 Type II or 1 Type III None Keyboard, Mouse, Serial, Parallel, CRT (VGA) 79/80 keys Integrated trackball	One type II and one type III, Built in microphone and speaker, Soundblaster and MS Sound System Compatible Keyboard, Mouse, Serial, Parallel, CRT, 1 jack for earphones or external speakers, docking connector, power connector 83 keys, 12 Functional keys, palmrest and 3 degree incline for comfort Large integrated Trackball (19mm)	Two type II or one type III Built in microphone and speaker, Soundblaster and MS Sound System Compatible Keyboard or Mouse, Serial, Enhanced Parallel, CRT, Stereo headphone jack, Stereo microphone jack, docking connector, power connector 83 keys, 12 Functional keys Front-mounted integrated Trackball
DESKTOP EXPANSION Cable Manager Docking Station	No No	Yes, Quick Dock II with serial, parallel, keyboard and mouse ports, CRT and DC in power. Power Dock II with Serial, parallel, mouse and keyboard ports, CRT, DC-in port and integrated AC adapter, 1 type II and 1 type III PCMCIA slot.	Yes, Cable Manager Globalyst Docking Station with two ISA slots, 2 external drive bays, 1 IDE fixed disk drive
VIDEO Video Memory Display Options	512KB 9.4" diagonal display DSTN: 640 x 480 x 256 colours (20 to 1 contrast ratio) Mono: 640 x 480 x 64 shades of grey (18 to 1 contrast ratio)	1MB 10.4" diagonal display TFT: 640 x 480 x 4000 colours (60 to 1 contrast ratio) DSTN: 640 x 480 x 256 colour (30 to 1 contrast ratio)	1MB 10.4" diagonal display SVGA: 800 x 600 x 64000 colours TFT: 640 x 480 x 256 colours
DIMENSIONS Size (HxWxD) Weight Battery Power AC power	1.77" x 10.55" x 8" 45mm x 268mm x 203mm 2.25kg / 4.7lbs NiMH battery, 2.5 hours battery life Lightweight autosensing adapter	2.2" x 11.3" x 8.94" 56mm x 287mm x 227mm 2.76kg / 6.2lbs NiMH battery, 3.5 - 4.5 hours battery life Lightweight autosensing adapter	2.1" x 11.7" x 9.3" 53mm x 297mm x 238mm 3.1kg / 6.9lbs NiMH battery, 3 - 5 hours battery life 6 - 10 hours with second battery Lightweight autosensing adapter
STANDARD FEATURES PC&C Features (communication) Green/Environmental Standards Bundled Software	Vistium Share Software pre-loaded, on-line services EPA Energy Star Compliant MS-DOS, MS-Windows, AT&T Mail AccessPlus, WinFax LITE, Wincomm LITE, Custom utilities, Enhanced Tourguide, Online documentation, AT&T Reach Out remote diagnostics, QA Plus Diagnostics, SystemSoft PCMCIA utilities, APM 1.1, Online to CompuServe		
OS Certification	MS-DOS/Windows, Windows for Workgroups, Windows 95	Notebook Configurator, Software Manager MS-DOS/Windows, Windows for Workgroups, Windows 95, Windows NT, Novell NetWare, IBM OS/2 Warp	Notebook Configurator, Software Manager, MS Video Runtime, OAG Flight Desk, Borland Sidekick MS-DOS/Windows, Windows for Workgroups, Windows 95, Windows NT, Novell NetWare, IBM OS/2 Warp